













Low Liquor Ratio Anjani @CO +

Soft Flow dyeing machine is a prime choice for dyeing wide range of fabric, it is designed and manufactured with the modern state of art and technology.

Anjani Soft Flows are capable of dyeing several variety of fabric from Low GSM to High GSM;it alsohas Double Rope dyeing Technology.

It has automatic and adjustable nozzle based on Fabric Nature.

In Corporating a New and Novel technology which reduce the process time and total energy consumption at the same time enhancing quality of the processed material.



Standard Feature:-

- Machine body and major parts wetted by dye liquid made of Stainless Steel 316 L highly corrosion and acid resistance.
- Highly efficient Vertical Heat Exchanger for fast heating and cooling and prevent scale formation.
- Highly efficient heavy duty stainless steel centrifugal pump with frequency control and also mechanical seal to avoid leakage.
- Machines are control via Industrial PLC with Air Conditional S.S. Control Panel to avoid the moisture formation inside the panel.

- Automatic Adjustable nozzle based on fabric nature.
- Mechanical Lock working with vessel internal pressure impact.
- Smart Dosing and Salt Dosing Function.
- Observing window with stainless metal grid.
- Internal main body washing system.
- LED Lighting System inside the main body.
- Seam Detection and cycle control system.
- Additional tank to reserve tank transfer.

Technical Data:-

- Stainless steel 316 L highly corrosion and acid resistance body.
- Maximum working temperature 140°c.
- Inner rotating fabric chamber for smooth and secure fabric transport.

Heating Rate:-

25° c - 100° c average 4° c/min. 100° c - 130° c average 2° c/min.

Cooling Rate:-

130°c - 100°c average 3°c/min. 100°c - 85°c average 2°c/min.



- Plot No. 983 & 984, Road No, 58, G.I.D.C. Sachin, Gujarat, India.
- +91 81548 88370 🕒 +91 70960 07670
- info@anjaniindustries.in www.anjaniindustries.in

AN ISO 9001:2015 CERTIFIED COMPANY